

Gamma/ L Series

ProMinent®

Smart and Versatile Solenoid Metering Pump

The ProMinent® gamma/ L is a microprocessor-based diaphragm solenoid metering pump capable of flows from **0.16 to 8.4 gph (0.59 to 32 l/h)** and pressures up to **290 psi (20 bar)**. The calibrated flow is displayed in gph or L/h. The large illuminated LCD display ensures that all displayed variables are easy to read.

Applications

- Bleach and other off-gassing fluid applications
- Water and wastewater treatment
- Highly automated processes in nearly all industries
- Cooling tower and boiler water treatment

Features & Benefits

- Microprocessor based technology for flexible control: Manual stroke length and frequency, Batch, Remote on/off, Contact Pulse, Analog
- Certified to **NSF/ANSI 61** (acrylic or PVDF liquid ends)
- 14-Day programmable timer
- Integrated Auto-degassing liquid ends ideal for off-gassing chemicals such as bleach
- Integral bleed valve eliminates priming issues
- Liquid end materials covering all chemicals
- Simple calibration allows pump to display flow rate and totalized flow
- Optional flow monitor for feed verification
- Universally compatible PVDF liquid ends
- Analog output of feed rate eliminates needs to check on the pump
- New Protimer software for programming timer from PC
- Access Codes to prevent unauthorized adjustment
- Capable of handling up to 3000 cps of viscous media such as polymers



Certified to
NSF/ANSI 61

ProMinent®

Visit our XTRANET <www.prominentxtranet.com> to:

- sign up for our electronic newsletter
- download literature and manuals
- validate your product warranty

Gamma/ L Series

Capacity data

Pump Version	Capacity at Maximum Backpressure					Capacity at 1/2 Maximum Backpressure					Pre-Primed Suction Lift		Max. Stroking Rate spm	Tubing Connectors ² O.D. x I.D. inches	Shipping Weight (higher weights are for SS)	
	psig	(bar)	U.S. GPH	l/h	ml/ stroke	psig	(bar)	U.S. GPH	l/h	ml/ stroke						
	ft	(m)	lbs	(kg)												
gamma/ L with standard liquid ends																
1000	145	(10)	0.19	(0.74)	0.07	73	(5)	0.21	(0.82)	0.08	19.6	(6)	180	1/4 x 3/16	7.5-8.6	(3.4-3.9)
2001 ³	290	(20)	0.29	(1.1)	0.10	145	(10)	0.37	(1.40)	0.13	19.6	(6)	180	1/4 x 3/16	6.4-7.9	(2.9-3.6)
1601	232	(16)	0.29	(1.1)	0.10	126	(8.75)	0.37	(1.4)	0.13	19.6	(6)	180	1/4 x 3/16	7.5-8.6	(3.4-3.9)
2002 ³	290	(20)	0.58	(2.2)	0.19	145	(10)	0.66	(2.5)	0.24	19.6	(6)	180	1/4 x 3/16	6.4-7.9	(2.9-3.6)
1602	232	(16)	0.55	(2.1)	0.19	126	(8.75)	0.66	(2.5)	0.24	19.6	(6)	180	1/4 x 3/16	7.5-8.8	(3.4-4.0)
1005	145	(10)	1.1	(4.4)	0.41	73	(5)	1.32	(5.0)	0.46	19.6	(6)	180	1/2 x 3/8	7.7-9.0	(3.5-4.1)
0708	101	(7)	1.9	(7.1)	0.66	50.5	(3.5)	2.22	(8.4)	0.78	19.6	(6)	180	1/2 x 3/8	7.7-11.0	(3.5-5.0)
0413	58	(4)	3.2	(12.3)	1.14	29	(2)	3.75	(14.2)	1.31	9.8	(3)	180	1/2 x 3/8	7.7-11.0	(3.5-5.0)
0220	29	(2)	5.0	(19.0)	1.76	14.5	(1)	5.52	(20.9)	1.94	6.5	(2)	180	1/2 x 3/8	7.7-11.0	(3.5-5.0)
1605	232	(16)	1.1	(4.1)	0.38	126	(8.75)	1.29	(4.9)	0.45	19.6	(6)	180	1/2 x 3/8	9.3-10.8	(4.2-4.9)
1008	145	(10)	1.8	(6.8)	0.63	73	(5)	2.19	(8.3)	0.76	19.6	(6)	180	1/2 x 3/8	9.5-12.8	(4.3-5.8)
0713	101	(7)	2.9	(11.0)	1.02	50.5	(3.5)	3.46	(13.1)	1.21	13.1	(4)	180	1/2 x 3/8	9.5-12.8	(4.3-5.8)
0420	58	(4)	4.5	(17.1)	1.58	29	(2)	5.04	(19.1)	1.77	9.8	(3)	180	1/2 x 3/8	9.5-12.8	(4.3-5.8)
0232 ¹	29	(2)	8.4	(32.0)	2.96	14.5	(1)	9.56	(36.2)	3.35	6.5	(2)	180	1/2 x 3/8	11.2-14.6	(5.1-6.6)

gamma/ L with auto-degassing liquid ends

1601	232	(16)	0.16	(0.59)	0.055	126	(8.75)	0.21	(0.78)	0.07	5.9	(1.8)	180	1/4 x 3/16	7.7	(3.5)
1602	232	(16)	0.37	(1.4)	0.13	126	(8.75)	0.45	(1.7)	0.16	6.9	(2.1)	180	1/4 x 3/16	7.7	(3.5)
1005	145	(10)	0.95	(3.6)	0.33	73	(5)	1.05	(4.0)	0.37	8.8	(2.7)	180	1/2 x 3/8	7.7	(3.5)
0708	101	(7)	1.74	(6.6)	0.61	50.5	(3.5)	1.98	(7.5)	0.69	6.5	(2.0)	180	1/2 x 3/8	7.7	(3.5)
0413	58	(4)	2.8	(10.8)	1.00	29	(2)	3.3	(12.6)	1.17	6.5	(2.0)	180	1/2 x 3/8	7.9	(3.6)
0220	29	(2)	4.3	(16.2)	1.50	14.5	(1)	4.7	(18.0)	1.67	6.5	(2.0)	180	1/2 x 3/8	7.9	(3.6)
1605	232	(16)	0.87	(3.3)	0.31	126	(8.75)	1.00	(3.8)	0.35	9.8	(3)	180	1/2 x 3/8	9.5	(4.3)
1008	145	(10)	1.66	(6.3)	0.58	73	(5)	1.98	(7.5)	0.69	9.8	(3)	180	1/2 x 3/8	9.5	(4.3)
0713	101	(7)	2.77	(10.5)	0.97	50.5	(3.5)	3.2	(12.3)	1.14	8.2	(2.5)	180	1/2 x 3/8	9.5	(4.3)
0420	58	(4)	4.12	(15.6)	1.44	29	(2)	4.6	(17.4)	1.61	8.2	(2.5)	180	1/2 x 3/8	9.5	(4.3)

(Note: Above capacities and suction lift refer to pumps tested on water at 115 VAC, 60 Hz, and an ambient temperature of 70°F (20°C). Higher specific gravity fluids will reduce suction lift. Capacities will be slightly reduced from published ratings if pumps are skid mounted.)

Higher viscosity fluids will reduce capacity. Liquid ends for highly viscous media have 10-20% less metering capacity and are not self-priming. Standard connectors are 1/2" MNPT or 5/8" hose barb. Positive suction is recommended.

¹ Not available with bleed valve.

² SS versions use 1/4" female threads except models 0220, 0420, and 0232 which use 3/8" female threads.

³ Only available in SS and Acrylic liquid ends.

Universal control cable necessary for external Beta control.

Liquid end materials in contact with media

	Pump head	Suction/Pressure connector	O-rings	Balls
PPE	Polypropylene	Polypropylene	EPDM	ceramic
PPB	Polypropylene	Polypropylene	Viton®	ceramic
NPE	Acrylic	PVC	EPDM	ceramic
NPB	Acrylic	PVC	Viton®	ceramic
PVT	PVDF	PVDF	PTFE	ceramic
TTT	PTFE with carbon	PTFE with carbon	PTFE	ceramic
SST	stainless steel	stainless steel	PTFE	ceramic

Auto-degassing version available in PP and NP only. Supplied with Hastelloy C valve springs, PVDF valve core.

Pump diaphragm with PTFE-coating.

Note: Viton® is a registered trademark of DuPont Dow Elastomers.

ProMinent®



ProMinent Fluid Controls, Inc. (US)

136 Industry Drive

Pittsburgh, PA 15275-1014

Tel: (412) 787-2484

Fax: (412) 787-0704

eMail: sales@prominent.us

www.prominent.us

Scan to download O&M