

ProMinent® Identcodes Solenoid Diaphragm Metering Pumps

Concept PLUS Identcode Ordering System

CNPb	Concept PLUS												
	Version	Capacity					Version	Capacity					
	1000	0.18 gph (0.7 l/h), 145 psi (10 bar)					0704	1.03 gph (3.9 l/h), 102 psi (7 bar)					
	1601	0.29 gph (1.1 l/h), 232 psi (16 bar)					0705	1.37 gph (5.2 l/h), 102 psi (7 bar)					
	1002	0.55 gph (2.1 l/h), 145 psi (10 bar)					0309	2.40 gph (9.0 l/h), 43.5 psi (3 bar)					
	1003	0.79 gph (3.0 l/h), 145 psi (10 bar)					0215	3.93 gph (14.9 l/h), 29 psi (2 bar)					
	Liquid end material:												
	PP	Polypropylene											
	NP	Acrylic/PVC											
	PV	PVDF											
	O-rings:												
	B	Viton® seals											
	E	EPDM seals											
	T	PTFE seals											
	Liquid end version:												
	0	Non-bleed version, no valve spring											
	1	Non-bleed version, with valve spring											
	2	With bleed valve, no valve spring (except 0704 models)											
	3	With bleed valve, with valve spring											
	Connection:												
	M	1/4" x 3/16"											
	N	3/8" x 1/4"											
	Logo:												
	0	With ProMinent® logo											
	Power Supply:												
A	1 ph 230 V 50/60 Hz (Euro plug)												
D	1 ph 115 V 50/60 Hz (US plug)												
4	1 ph 230 V 50/60 Hz (US plug) (consult factory for pricing)												
Control Option:													
0	Standard (w/o external control)												
B	With external and level input retrofit kit, fitted, without level switch												
Accessories:													
1	With accessories (foot valve, injection valve, tubing)												
Control Variant:													
0	Standard												
Approval:													
01	CE												
07	MET												
11	MET + NSF 61												
CNPb	1000	PP	B	0	M	0	A	0	1	0	01		