

ProMinent® Identcodes Motor Driven Metering Pumps

Makro TZ Identcode Ordering System

TZMb	Drive Type:													
	H	Main Drive												
		Pump Type:												
		120260	82 gph, 174 psi	070720	228 gph, 100 psi									
		120340	108 gph, 174 psi	070860	272 gph, 100 psi									
		120430	136 gph, 174 psi	040840	266 gph, 58 psi									
		120510	162 gph, 174 psi	041100	348 gph, 58 psi									
		070430	136 gph, 100 psi	041400	443 gph, 58 psi									
		070570	180 gph, 100 psi	041670	529 gph, 58 psi									
		Liquid end material:												
		PC	PVC											
		PP	Polypropylene											
		SS	Stainless Steel											
		TT	PTFE + 25% carbon											
		Seal material:												
		T	PTFE											
		Positive displacement element:												
		1	Standard composi diaphragm with rupture indicator											
		Liquid end version:												
		0	No valve springs											
		1	With valve springs											
		Hydraulic connection:												
		0	Standard connection	3	PVDF union nut and insert									
		1	PVC union nut and insert	4	SS union nut and insert									
		2	PP union nut and insert											
		Versions:												
		0	with ProMinent® logo											
		Electrical power supply:												
		0	add-on drive unit without electrical connection											
		4	No motor, with 56 C flange											
		Enclosure rating:												
		0	IP 55 (Standard) ISO class F											
		Stroke sensor:												
		0	No stroke sensor											
		1	With stroke sensor (Namura)											
		Stroke length adjustment:												
		0	0 Stroke length adjustment, man.											
		1	230 V stroke actuator											
		2	115 V stroke actuator											
		3	230 V 0-20 mA stroke controller											
		4	230 V 4-20 mA stroke controller											
		5	115 V 0-20 mA stroke controller											
		6	115 V 4-20 mA stroke controller											
		Applications												
		0	Standard											
TZMb	H	120260	PC	T	1	0	0	0	0	0	0	0	0	0