

ProMinent® Identcodes Motor Driven Metering Pumps

Sigma/ 2 HK Basic Identcode Ordering System

S2Ba	Drive Type												
	HK	Main Drive/Plunger											
		Version: Capacity:											
		32002	0.6 gph (2.3 l/h), 4640 psi (320 bar)	04522	7.0 gph (27.6 l/h), 652 psi (45 bar)								
		14006	1.8 gph (7.1 l/h), 2030 psi (140 bar)	02541	13.0 gph (49.2 l/h), 363 psi (25 bar)								
		07012	3.9 gph (14.8 l/h), 1015 psi (70 bar)	10006	2.0 gph (7.6 l/h), 1450 psi (100 bar)								
		04022	7.0 gph (26.5 l/h), 580 psi (40 bar)	05016	5.2 gph (20 l/h), 725 psi (50 bar)								
		23004	1.2 gph (4.8 l/h), 3335 psi (230 bar)	02534	10.7 gph (40.8 l/h), 363 psi (25 bar)								
		10011	3.4 gph (13.1 l/h), 1450 psi (100 bar)	01264	20.1 gph (76 l/h), 174 psi (12 bar)								
		Liquid end material:											
		SS	316 Stainless Steel										
		Seal:											
		T	PTFE seal										
		Plunger assembly:											
		4	Plunger (Ceramic)										
		Liquid end version:											
		0	Without valve springs										
		1	With 2 valve springs (Hastelloy C4, 1 psig)										
		Hydraulic connections:											
		0	Standard (In accordance with technical data)										
		Logo:											
		0	Standard with logo										
		Motor mount:											
		2	Without motor, with NEMA 56C flange										
		Enclosure rating:											
		0	Standard										
		Stroke sensor:											
		0	Without stroke sensor (Standard)										
		1	With Pacing relay (Consult Factory)										
		Stroke length adjustment:											
		0	Manual (Standard)										
		1	with 3P stroke positioning motor, 230 V 50/60 Hz										
		2	with 3P stroke positioning motor, 115 V 50/60 Hz										
		4	W/ stroke positioning motor 4-20 mA, 230 V 50/60 Hz										
		6	W/ stroke positioning motor 4-20 mA, 115 V 50/60 Hz										
S2Ba	HK	32002	SS	T	4	0	0	0	2	0	0	0	