

# DulcoFlex DFD Series

## High flows and high pressures with the DFD series pumps

The **DulcoFlex DFD** is a hose pump designed for pressures up to **232 psi** and flow rates up to **225 gpm**. The unique shoe design is made of steel for smoother and cooler compression. The **DFD** uses safe **DulcoLube** oil for the shoe lubrication. With suction lifts up to **29 feet**, the **DulcoFlex DFD** is a great choice for difficult pumping applications.

## Applications

- Sludge transfer
- Lime slurry
- NaOCl transfer
- Inks
- Dyes
- Acids
- Caustics
- Wine barrel filling
- Water & Waste water
- Chemicals
- Breweries & Wineries
- Pulp & Paper




## Features & Benefits

- Sizes: 25, 32, 40, 60, 70, 100mm
- Flows to 225 gpm
- Suction lifts up to 29 ft.
- Disaster proof hose connections
- DulcoLube food grade glycerin lubricant
- Designed heat sink fins for cooler operation
- Steel shoes for a smoother and cooler compression
- Run dry capabilities

# DulcoFlex DFD Series

## DFD Series Flow Rates



## Pump Capacities

	DFD25	DFD32	DFD40	DFD60	DFD70	DFD100
<b>Compression</b>	Shoe	Shoe	Shoe	Shoe	Shoe	Shoe
<b>Connection</b>	1"	1 ½"	1 ½"	2 ½"	3"	4"
<b>Capacity gal/rev</b>	0.08	0.16	0.37	0.85	1.76	5.28
<b>Max Flow gpm</b>	12	20	30	84	130	225
<b>Reinforced Hoses</b>	Natural Rubber			Hypalon		
	Nitrile Buna Rubber			Natural Rubber Food Grade		
	EPDM			Nitrile Buna Rubber Food Grade		
<b>Max Pressure Reinforced Hose</b>	232 psi	232 psi	232 psi	232 psi	232 psi	232 psi