













NOTES:

- 1. ALL PIPING AND FITTINGS SHALL BE 1/2" SCH. 80 CPVC SOCKET WELD WITH VITON SEALS UNLESS OTHERWISE REQUIRED BY COMPONENTS.
- 2. ALL VALVES TO BE VENTED.
- 3. ALL DIMENSIONS ARE IN INCHES AND ARE SHOWN FOR REFERENCE ONLY.

Α	05/14/09	REVISED PER BASIC SKID	GJS						
0	02/08/08	FIRST ISSUE	GJS						
REV	DATE	DESCRIPTION	BY	APPD	REVD				
REVISIONS									

CUSTOMER PROMINENT FLUID CONTROLS INC. (PRE-ENGINEERED SYSTEM)

JOB No 7749079 PURCHASE ORDER No

TITLE SS1-B_FLOOR_050_CPVC\VITON-V_DEGASS_PD **GENERAL ARRANGEMENT**

THIS DRAWING IS THE PROPERTY OF PROMINENT FLUID CONTROLS INC. AND SHALL NOT BE COPIED OR TRANSFERRED WITHOUT THE WRITTEN CONSENT OF PROMINENT FLUID CONTROLS INC.

ENGINEERS SEAL





	PITTSBURGH, PA USA			WWW.PROMINENT.US				
	PROMINENT FLUID CONTROLS LTD. 490 SOUTHGATE DRIVE. GUELPH, ONTARIO, CANADA N1H 6J3			PROMINENT FLUID CONTROLS INC.				
				RIDC PARK WEST				
				136 INDUSTRY DRIVE, PITTSBURGH P.A., USA. 15275				
	TEL. 519 836 5692	FAX. 519 836 5226	TEL. 4	112 787 2484 F	AX. 412 787 0704			
	DESIGNED	DESIGNED GJS		APPROVED				
	DRAWN	GJS	SCA	LE N	N.T.S.			
	CHECKED	DTH	DAT	E 02	2/08/08			
				REV	PAGE			
Ä	0070 200			^	4 /4			

MAXIMUM TESTING PRESSURE = 150 PSI MAXIMUM OPERATING PRESSURE = 150 PSI CHEMICAL SERVICE =

7749079-200

1/1 Α