


MAXIMUM TESTING PRESSURE = MAXIMUM OPERATING PRESSURE = 145-150 PSI

CHEMICAL SERVICE =



NOTES:

- 1. ALL PIPING AND FITTINGS SHALL BE 1/2" SCH. 80 CPVC SOCKET WELD WITH VITON SEALS UNLESS OTHERWISE REQUIRED BY COMPONENTS.
- 2. ALL VALVES TO BE VENTED.
- 3. ALL DIMENSIONS ARE IN INCHES AND ARE SHOWN FOR REFERENCE ONLY.

					-				
Α	05/14/09	REVISED PER BASIC SKID	GJS						
0	02/08/08	FIRST ISSUE	GJS						
REV	DATE	DESCRIPTION	BY	APPD	REVD				
REVISIONS									

CUSTOMER PROMINENT FLUID CONTROLS INC. (PRE-ENGINEERED SYSTEM)

JOB No 7749082 PURCHASE ORDER No

> SS1-A_FLOOR_050_CPVC\VITON-V GENERAL ARRANGEMENT

THIS DRAWING IS THE PROPERTY OF PROMINENT FLUID CONTROLS INC. AND SHALL NOT BE COPIED OR TRANSFERRED WITHOUT THE WRITTEN CONSENT OF PROMINENT FLUID CONTROLS INC.

PITTSBURGH PAUSA

ENGINEERS SEAL

TITLE

150 PSI DWG No





WWW PROMINENT US

	FILL DOUGH, FA OSA			WWW.FINOWIINLINT.03			
	PROMINENT FLUID CONTROLS LTD.			PROMINENT FLUID CONTROLS INC.			
	490 SOUTHGATE DRIVE. GUELPH, ONTARIO, CANADA N1H 6J3			RIDC PARK WEST 136 INDUSTRY DRIVE, PITTSBURGH P.A., USA. 15275			
	TEL. 519 836 5692	FAX. 519 836 5226	TEL. 4	112 787 2484 I	FAX. 412 787 0704		
	DESIGNED GJS			APPROVED			
	DRAWN	GJS	SCA	11.1.0.			
	CHECKED	DTH	DAT				
				REV	PAGE		
7749082-200				Α	1/1		
	l l						