


ISOMETRIC VIEW



## NOTES:

- 1. ALL PIPING AND FITTINGS SHALL BE 1/2" SCH. 80 CPVC SOCKET WELD WITH VITON SEALS UNLESS OTHERWISE REQUIRED BY COMPONENTS.
- 2. ALL VALVES TO BE VENTED.
- 3. ALL DIMENSIONS ARE IN INCHES AND ARE SHOWN FOR REFERENCE ONLY.

Α	05/14/09	REVISED PER BASIC SKID	GJS					
0	02/08/08	FIRST ISSUE	GJS					
REV	DATE	DESCRIPTION	BY	APPD	REVD			
REVISIONS								
CUSTOMER PROMINENT FLUID CONTROLS INC.								
(PRE-ENGINEERED SYSTEM)								

PURCHASE ORDER No

JOB No 7749110

> SS1-F\_FLOOR\_050\_CPVC\VITON-V GENERAL ARRANGEMENT

THIS DRAWING IS THE PROPERTY OF PROMINENT FLUID CONTROLS INC. AND SHALL NOT BE COPIED OR TRANSFERRED WITHOUT THE WRITTEN CONSENT OF PROMINENT FLUID CONTROLS INC.

ENGINEERS SEAL

TITLE





	PITTS	BURGH, PA USA	V	VWW.PROMINI	ENT.US	
	PROMINENT FLUID CONTROLS LTD.		PROMINENT FLUID CONTROLS INC.			
	490 SOUTHGATE DRIVE.		RIDC PARK WEST			
	GUELPH, ONTARIO, CANADA		136 INDUSTRY DRIVE,			
	N1H 6J3	N1H 6J3		PITTSBURGH P.A., USA. 15275		
	TEL. 519 836 5692	FAX. 519 836 5226	TEL. 4	12 787 2484 F	FAX. 412 787 0704	
	DESIGNED	GJS	APPROVED			
	DRAWN	GJS	SCA	LE N	N.T.S.	
	CHECKED	DTH	DAT	E 02	02/08/08	
				REV	PAGE	
7 4	10110 000			4.14		

SIDE VIEW

MAXIMUM TESTING PRESSURE = 150 PSI DWG No MAXIMUM OPERATING PRESSURE = 58 PSI CHEMICAL SERVICE =

7749110-200 Α

		Ī
		60.0
	50	.00
	12.00	

FRONT VIEW