





## NOTES:

- 1. ALL PIPING AND FITTINGS SHALL BE 1/2"(20MM) SR232 PVDF FUSION WELD WITH VITON SEALS UNLESS OTHERWISE REQUIRED BY COMPONENTS.
- 2. ALL DIMENSIONS ARE IN INCHES AND ARE SHOWN FOR REFERENCE ONLY.

Α	08/19/09	REVISED PER NEW PARTS	ALS						
0	01/21/08	FIRST ISSUE	GJS						
REV	DATE	DESCRIPTION	BY	APPD	REVD				
REVISIONS									

## CUSTOMER PROMINENT FLUID CONTROLS INC. (PRE-ENGINEERED SYSTEM)

JOB No 7749248 PURCHASE ORDER No

> SS2-C\_FLOOR\_050\_PVDF\VITON **GENERAL ARRANGEMENT**

THIS DRAWING IS THE PROPERTY OF PROMINENT FLUID CONTROLS INC. AND SHALL NOT BE COPIED OR

ENGINEERS SEAL

TITLE





	PILIS	SBURGH, PA USA	V	VVVVV.PROMINE	EN1.05	
	PROMINENT FLUID CONTROLS LTD.		PROMINENT FLUID CONTROLS INC.			
	490 SOUTHGATE DRIVE.		RIDC PARK WEST			
	7.1		136 INDUSTRY DRIVE, PITTSBURGH P.A., USA. 15275			
	TEL. 519 836 5692	FAX. 519 836 5226	TEL. 4	12 787 2484 F	AX. 412 787 0704	
	DESIGNED	GJS	APP	ROVED		
	DRAWN	vn GJS		SCALE N.T.S.		
				- 04	01/21/08	
	CHECKED	DTH	DAT	E 01	/21/08	
	CHECKED	DIH	DAT	REV	/21/08 PAGE	

SIDE VIEW

MAXIMUM TESTING PRESSURE = 150 PSI MAXIMUM OPERATING PRESSURE = 29-150 PSI CHEMICAL SERVICE =

7749248-200

А

			<b>A</b>
		46. 43.00	.00
		<u> </u>	
		8.00	•

FRONT VIEW