

# CBR Chlorine Sensors

Reliable measurement of Free Chlorine using membraneless amperometric sensor technology



**ProMinent®** offers its new line of Free Chlorine sensors, the CBR series. These sensors were developed for measurement in water with higher pH, process water, cooling tower water, etc. The membrane covered Amperometric sensor measures both HOCl and OCl at pH values up to 9.5 without the need for buffers or reagents.

## Technical Data

- Measured Variable: Free Cl, Free Br, and Bound BR
- pH Range: 5.0 - 9.5
- Temp Range: 41° F - 113° F (5° C- 45° C)
- Max Pressure: 14.5 psi
- Flow: 8 -16 gph
- Output signal: 4-20 mA
- Controller: D1C / D2C / DAC
- Calibration: DPD 1

## Applications

- Potable Water
- Cooling towers
- Wastewater
- High pH water

## Ordering Information

- CBR 1 mA 0.5 PPM range 0.01 ... 0.50 PPM p/n 1038016
- CBR 1 mA 2.0 PPM range 0.02 ... 2.00 PPM p/n 1038015
- CBR 1 mA 10.0 PPM range 0.10 ... 10.0 PPM p/n 1038014

| Metering Pumps | Process Instrumentation | Engineered Metering Systems |

**ProMinent Fluid Controls, Inc.**

136 Industry Drive • Pittsburgh, PA 15275 USA

(412) 787-2484 • Fax: (412) 787-0704

email: [sales@prominent.us](mailto:sales@prominent.us) • [www.prominent.us](http://www.prominent.us)

© 2013 ProMinent Fluid Controls, Inc. All Rights Reserved.

PN: 7750233

CBR\_Sensors.indd rev2 06/19/2013

**ProMinent®**

