

Concept b Series

Economical metering pump solutions!



The **ProMinent® Concept b** series covers a capacity range of **0.19 to 4.33 GPH (0.7 to 16.4 L/h)** at pressures up to **232 psi (16 bar)**.

Its compact construction and features make it ideal for use in flow proportional or on/off control applications. The Concept b mounts easily onto a tank or wall bracket.

Adjustment of the pump capacity is via the stroke length in the range of 10-100 % or can be set at 1 of the 4 stroke frequency settings. This gives an adjustment ratio of 40:1.

Features & Benefits

- NSF 61/50 approved
- Low cost opens up opportunities in the most basic applications
- PVDF wetted ends eliminate compatibility concerns
- Integral bleed valve prevents “loss of prime”
- Lowest maintenance costs in its class
- External control via dry contact pulse (1:1)
- Wetted end materials: PP, Acrylic/PVC or PVDF

Applications

- Swimming pools
- Spas, fountains and spray pads
- Cooling towers
- Boiler feed applications
- General Chlorination
- Municipal and industrial wastewater
- Water disinfection
- Biocide feed
- “Pump on a drum” applications

Concept b Series

Technical data

Capacity Data											
Pump Version	Capacity at Maximum Back Pressure				mL/ stroke	Max. Stroking Rate	Pre-Primed Suction Lift		Tubing Connectors O.D. x I.D.	Shipping Weight (approx.)	
	psig	(bar)	GPH	(L/h)			ft.	(m)		lbs.	(kg)
CNPb											
1000	145	(10)	0.19	(0.7)	0.07	180	20	(6)	1/4 x 3/16	3.97	(1.8)
1601	232	(16)	0.29	(1.1)	0.10	180	20	(6)	1/4 x 3/16	3.97	(1.8)
1002	145	(10)	0.63	(2.4)	0.19	180	16	(5)	1/4 x 3/16	3.97	(1.8)
1003	145	(10)	0.79	(3.0)	0.21	240	16	(5)	1/4 x 3/16	3.97	(1.8)
0704	102	(7)	1.03	(4.0)	0.41	180	13	(4)	1/4 x 3/16	3.97	(1.8)
0705	102	(7)	1.37	(5.2)	0.36	240	13	(4)	1/4 x 3/16	3.97	(1.8)
0309	44	(3)	2.38	(9.0)	0.83	180	20	(6)	3/8 x 1/4	3.97	(1.8)
0215	22	(1.5)	4.33	(16.4)	1.45	180	5	(1.5)	3/8 x 1/4	3.97	(1.8)

External pulse contact retrofit available as an option (P/N 1022000)

NSF 50 certification only applies to NPB0 & NPB2 liquid ends

Identity code pump configuration

CNPb	Concept PLUS											
	Version	Capacity					Version	Capacity				
	1000	0.19 gph (0.7 l/h), 145 psi (10 bar)					0704	1.03 gph (4.0 l/h), 102 psi (7 bar)				
	1601	0.29 gph (1.1 l/h), 232 psi (16 bar)					0705	1.37 gph (5.2 l/h), 102 psi (7 bar)				
	1002	0.63 gph (2.4 l/h), 145 psi (10 bar)					0309	2.38 gph (9.0 l/h), 44 psi (3 bar)				
	1003	0.79 gph (3.0 l/h), 145 psi (10 bar)					0215	4.33 gph (16.4 l/h), 22 psi (1.5 bar)				
	Liquid end material:											
	PP	Polypropylene										
	NP	Acrylic/PVC										
	PV	PVDF										
	O-rings:											
	B	Viton® seals										
	E	EPDM seals										
	T	PTFE seals										
	Liquid end version:											
	0	Non-bleed version, no valve spring										
	1	Non-bleed version, with valve spring										
	2	With bleed valve, no valve spring (except 0704 models)										
	3	With bleed valve, with valve spring										
	7	Auto-degassing										
	Connection:											
	M	1/4" x 3/16"										
	N	3/8" x 1/4"										
	Logo:											
	0	With ProMinent logo										
	Power Supply:											
	A	1 ph 230 V 50/60 Hz (Euro plug)										
	D	1 ph 115 V 50/60 Hz (US plug)										
	4	1 ph 230 V 50/60 Hz (US plug) (consult factory for pricing)										
	Control Option:											
	0	Standard (w/o external control)										
	B	With external and level input retrofit kit, fitted, without level switch										
	Accessories:											
	1	With accessories (foot valve, injection valve, tubing)										
	Control Variant:											
	0	Standard										
Approval:												
01	CE											
07	MET											
11	MET + NSF 61											
CNPb	1000	PP	B	0	M	0	A	0	1	0	01	

© 2016 ProMinent Fluid Controls, Inc. All Rights Reserved. PN: 7750012 Concept_b.indd rev7 06/02/2022

ProMinent®

ProMinent Fluid Controls, Inc. (USA)
136 Industry Drive • Pittsburgh, PA 15275
(412) 787-2484 • email: sales@prominent.us
www.prominent.us

ProMinent Fluid Controls, Ltd. (Canada)
490 Southgate Drive • Guelph, N1G 4P5
(519) 836-5692 • Fax: (519) 836-5226 • Toll Free 1-888-709-9933
email: sales@prominent.ca • www.prominent.com