

DCM 5 Series Controller

Stay Connected and Stay in Control of Your Aquatics Facility!



The **ProMinent® DCM 5 Series** controller is the perfect partner for remote monitoring and controlling water parameters and processes. The **DCM 5 Series** precision, flexibility and uncompromising quality represent a world-class IIoT solution to ensure a safe and healthy water experience for your customers and peace of mind for you.

Features & Benefits

Stay Connected

- Receive email and text alarms
- Make changes from your smartphone, tablet or computer
- No apps required to connect and control
- Automatic emailing of data logs
- WiFi, RS485, Modbus, BACnet and 4G capable

Stay in Control

- Monitor and control
 - Combined chlorine
 - UV systems
 - VFDs
- Precision chemical feed
 - Proportional and PID control strategies
 - Control output of ProMinent pumps

Stay Safe

- Configurable digital interlocking to flowmeter and circ pump
- 29 discrete assignable passwords at three access tiers
- Simultaneous monitoring and control of ORP and PPM

World-Class Accuracy

- pH sensor accurate to 0.04 SU per NSF
- PPM sensor compliant to USEPA 334.0

Applications

- Swimming pools, Therapy pools & Hot tubs
- Water parks & Splash pads
- Amusement Park Attractions

Ordering Information

- **DCM 510** - pH, ORP and Temp (P/N: 1080771)
- **DCM 511** - pH, ORP and PPM on non-stabilized (CYA) water (P/N: 1080772)
- **DCM 512** - pH, ORP, Free, Total and Combined Chlorine on non-stabilized (CYA) water (P/N: 1080773)
- **DCM 513** - pH, ORP and PPM on CYA stabilized water (P/N: 1080774)



DCM 5 Series Controller

Specifications

| Operator Interface | | |
|--------------------|--|--|
| Remote | Fully interactive Ethernet TCP/IP graphical interface with security access codes | |
| Local | 2 line, 16 character LCD display, 5 buttons, 2 LEDs: Steady Blue = "OK", Flashing RED = "ALARM" | |
| Sensors | | |
| Included Sensors | pH, ORP, Temperature | |
| Optional Sensors | Free Chlorine, Total Chlorine, Calculated Combined Chlorine, Salt Generated Free Chlorine,Stabilized Chlorine, Conductivity, Bromine, Feed Verification, Corrosion, Flow Rate, Water Level | |
| Field Upgrades | Sensor input modules are available for field upgrades. | |
| Inputs | | |
| Digital Inputs | 8, (7 Fully Configurable) | |
| Analog Inputs | 7 Standard (Configurable Options) + 4 Optional (additional Temp, 4-20mA and 2 corrosion | Example: 1 Cond, 1 Temp, 1 pH, 1 ORP, 1 FAC, 1 TRC, 1 4-20mA Flow, 2 Corrosion |
| Outputs | | |
| Control Relays | 5 (Fully Assignable) | |
| | 1. Acid 2. Oxidant 3. Chlorine boost / Caustic feed 4. Probe Wash / Alarm | 5. Filter Aid / Flow switch test & verify 6. Auto fill 7. Heater control 8. UV control |
| | Interlocked with sample and recirc flow when used for chemical feed. | |
| Digital Outputs | 4 (Fully assignable as dry contact sets or variable frequency pump) 1. UV 2. Pump / VFD control 3. Chlorine / Ozone generator 4. Alarm / Eco! Mode mode for Recirc Pump | |
| | Base feed available if sensor disconnected | |
| Analog Outputs | 2 (Optional isolated, 4-20mA) | |
| Control | | |
| | On/Off ORP assisting residual P/PID/PID Eco! Mode Event timers UV boost / VFD control | Chlorine boost / Ozone control Flow restored delayed (adjustable) Emergency Off for recirculation pump Autofill Chemical feed verification (optional) Pulsed pump speed |
| Communication | | |
| | HTML server on board (standard) 10Base T, TCP/IP Ethernet ,Optional Wireless 3G Cellular, Smartphone / iPad HTML, Micro Web Server with DHCP or user definable IP address | |
| Security | | |
| | Local and remote access protected by access codes | |
| SYSTEM | | |
| Power | 120 or 230 VAC, 60/50 Hz, 5A/3A, single phase only | |
| Fusing | 5 amps @ 120 VAC or 2.5 Amps @ 230 VAC | |
| Surge Suppression | Relay 2-5 N.O. contacts snubbed @ 0.1 uF, 150 ohm | |
| Accessory Power | 15-22 VDC, Unregulated, Thermally Fused @ 50 mA | |
| Enclosure | Non-metallic, NEMA 4X / 7.5" x 11.3" x 5.5" (WxHxD) | |
| Convenience | Save and restore of "last known good" parameters Multiple pre-loaded configurations and browser views | |
| Certifications | | |
| | NSF/ANSI/CAN Standard 50 | |
| | UL 61010-1 | |
| | CSA CAN/CSA-22.2 No. 61010-1-12 | |
| Warranty | | |
| | 5 years on electronics | |
| | 2 years on ORP, pH sensors | |
| | 1 year on all other parts | |

© 2020 ProMinent Fluid Controls, Inc. · All Rights Reserved · PN: 7750003 · DCM_5_Series.indd rev6 · 12/8/2020