

DULCOMETER Controllers

Reliable process measurement and control



wall mount controller package (D1Cb)

ProMinent® DULCOMETER analyzers provide precise monitoring or controlling of process variables for Municipal and Industrial applications. **DULCOMETER** products encompass a complete range of quality instrumentation from single channel transmitters to multi-channel disinfection controllers.

ProMinent® amperometric technology surpasses many of today's colorimetric methods by providing real time, on-line measurement without reagents or buffer solutions. Process variables include free and total chlorine, fluoride, chlorine dioxide, chlorite, pH, ORP, hydrogen peroxide, peracetic acid and ozone.

Complete your application by choosing one of our standard, pre-engineered monitoring or control packages, which comes fully assembled including controller, sensors, sensor holder, wiring, backpanel and quickstart guide.

Features & Benefits

- Chlorine control (with amperometric sensors)
EPA method 334.0 compliant
- Controls and/or monitors 14 on-line process variables
- Available in wall mount or panel mount
- One programmable analog output
- Standard pre-designed system packages
- On/Off, Proportional or PID control
- Two pump pacing relays
- Alarm and relay control



panel mount controller (D1Cc)

DULCOMETER Controllers

Selection aid for ProMinent® DULCOTEST sensors

Measured variable	Measured range	Maximum Pressure	Temperature Range
Fluoride	0.05 - 10 ppm	102 psi (7 bar)	34° - 95° F (1° - 35° C)
Free chlorine	0.01 - 0.50 ppm	14.5 psi (1 bar)	41° - 113° F (5° - 45° C)
	0.02 - 2 ppm	14.5 psi (1 bar)	41° - 113° F (5° - 45° C)
	0.05 - 5 ppm	14.5 psi (1 bar)	41° - 113° F (5° - 45° C)
	0.10 - 10 ppm	14.5 psi (1 bar)	41° - 113° F (5° - 45° C)
	0.20 - 20 ppm	14.5 psi (1 bar)	41° - 113° F (5° - 45° C)
	0.50 - 50 ppm	14.5 psi (1 bar)	41° - 113° F (5° - 45° C)
	1 - 100 ppm	14.5 psi (1 bar)	41° - 113° F (5° - 45° C)
Total chlorine	0.01 - 0.05 ppm	44 psi (3 bar)	41° - 113° F (5° - 45° C)
	0.02 - 2 ppm	44 psi (3 bar)	41° - 113° F (5° - 45° C)
	0.05 - 5 ppm	44 psi (3 bar)	41° - 113° F (5° - 45° C)
	0.10 - 10 ppm	44 psi (3 bar)	41° - 113° F (5° - 45° C)
Bromine	0.01 - 0.50 ppm	44 psi (3 bar)	41° - 113° F (5° - 45° C)
	0.02 - 2 ppm	44 psi (3 bar)	41° - 113° F (5° - 45° C)
	0.20 - 10 ppm	44 psi (3 bar)	41° - 113° F (5° - 45° C)
Chlorine dioxide	0.01 - 0.50 ppm	14.5 psi (1 bar)	41° - 113° F (5° - 45° C)
	0.02 - 2 ppm	14.5 psi (1 bar)	41° - 113° F (5° - 45° C)
	0.10 - 10 ppm	14.5 psi (1 bar)	41° - 113° F (5° - 45° C)
Chlorite	0.02 - 0.50 ppm	14.5 psi (1 bar)	34° - 104° F (1° - 40° C)
	0.10 - 2 ppm	14.5 psi (1 bar)	34° - 104° F (1° - 40° C)
Ozone	0.02 - 2 ppm	14.5 psi (1 bar)	41° - 104° F (5° - 40° C)
Dissolved oxygen	0 - 10 ppm	14.5 psi (1 bar)	32° - 122° F (0° - 50° C)
	0 - 20 ppm	14.5 psi (1 bar)	32° - 122° F (0° - 50° C)
Peracetic acid	1 - 200 ppm	44 psi (3 bar)	34° - 113° F (1° - 45° C)
	10 - 2,000 ppm	44 psi (3 bar)	34° - 113° F (1° - 45° C)
Hydrogen peroxide	2 - 200 ppm	14.5 psi (1 bar)	32° - 113° F (0° - 45° C)
	20 - 2,000 ppm	14.5 psi (1 bar)	32° - 113° F (0° - 45° C)

Note: pH, ORP, Temperature, Conductivity sensors also available. Please consult catalog or factory for selection.

Related Products

DULCOMETER DMT

The DMT is a compact 2-wire transmitter for measured variables pH, Redox, Conductive Conductivity, Temperature, and Chlorine.

DULCOMETER Compact

The Compact is an on-line controller/monitor for pH and ORP measurement or control. Control is in one direction only and can be programmed for proportional or PID control. Temperature compensation is available.

DULCOMETER DDC

The Dulcometer Disinfection Controller is a measuring and control system for up to five variables including pH, ORP, Temperature, Free Chlorine and Total Chlorine. A central DDC unit can control up to 16 remote locations.

© 2018 ProMinent Fluid Controls, Inc. All Rights Reserved. PN: 7750240 Dulcometer_Controllers.indd rev2 04/27/2016