

DULCOMETER® D1C/D2C

Reliable process measurement and control

ProMinent® DULCOMETER® analyzers provide precise monitoring or controlling of process variables for Municipal and Industrial applications. DULCOMETER® products encompass a complete range of quality instrumentation from single channel transmitters to multi-channel disinfection controllers.

ProMinent® amperometric technology surpasses many of today's colorimetric methods by providing real time, on-line measurement without reagents or buffer solutions. Process variables include free and total chlorine, fluoride, chlorine dioxide, chlorite, hydrogen peroxide, peracetic acid and ozone.

Select from single variable transmitters (**DMT**), single variable controllers (**D1C**), dual variable controllers (**D2C**) and multi-variable controllers (**DDC**). Complete the application by choosing one of our standard, pre-engineered monitoring or control packages which comes fully assembled including controller, sensors, sensor holder, wiring, backpanel and quickstart guide.



Features & Benefits

- Chlorine control (with amperometric sensors) **EPA method 334.0 compliant**
- Controls and/or monitors 14 on-line process variables
- Temperature and pH correcting values
- One programmable analog output (D1Cb)
- Two programmable analog outputs (D1Ca & D2C)
- On/Off, Proportional or PID control
- Alarm and relay control
- Feed forward control (D1Ca)
- Standard pre-designed system packages

ProMinent®

Visit our XTRANET <www.prominentxtranet.com> to:

- sign up for our electronic newsletter
- download literature and manuals
- validate your product warranty

DULCOMETER® D1C/D2C

Selection aid for ProMinent® sensors

Measured variable	Measured range	Maximum Pressure	Temperature Range
Fluoride	0.05 - 10 ppm	102 psi (7 bar)	34° - 95°F (1° - 35°C)
Free chlorine	0.01 - 0.50 ppm	14.5 psi (1 bar)	41° - 113°F (5° - 45°C)
	0.02 - 2 ppm	14.5 psi (1 bar)	41° - 113°F (5° - 45°C)
	0.05 - 5 ppm	14.5 psi (1 bar)	41° - 113°F (5° - 45°C)
	0.10 - 10 ppm	14.5 psi (1 bar)	41° - 113°F (5° - 45°C)
	0.20 - 20 ppm	14.5 psi (1 bar)	41° - 113°F (5° - 45°C)
	0.50 - 50 ppm	14.5 psi (1 bar)	41° - 113°F (5° - 45°C)
	1 - 100 ppm	14.5 psi (1 bar)	41° - 113°F (5° - 45°C)
Total chlorine	0.01 - 0.05 ppm	44 psi (3 bar)	41° - 113°F (5° - 45°C)
	0.02 - 2 ppm	44 psi (3 bar)	41° - 113°F (5° - 45°C)
	0.05 - 5 ppm	44 psi (3 bar)	41° - 113°F (5° - 45°C)
	0.10 - 10 ppm	44 psi (3 bar)	41° - 113°F (5° - 45°C)
Bromine	0.01 - 0.50 ppm	44 psi (3 bar)	41° - 113°F (5° - 45°C)
	0.02 - 2 ppm	44 psi (3 bar)	41° - 113°F (5° - 45°C)
	0.20 - 10 ppm	44 psi (3 bar)	41° - 113°F (5° - 45°C)
Chlorine dioxide	0.01 - 0.50 ppm	14.5 psi (1 bar)	41° - 113°F (5° - 45°C)
	0.02 - 2 ppm	14.5 psi (1 bar)	41° - 113°F (5° - 45°C)
	0.10 - 10 ppm	14.5 psi (1 bar)	41° - 113°F (5° - 45°C)
Chlorite	0.02 - 0.50 ppm	14.5 psi (1 bar)	34° - 104°F (1° - 40°C)
	0.10 - 2 ppm	14.5 psi (1 bar)	34° - 104°F (1° - 40°C)
Ozone	0.02 - 2 ppm	14.5 psi (1 bar)	41° - 104°F (5° - 40°C)
Dissolved oxygen	0 - 10 ppm	14.5 psi (1 bar)	32° - 122°F (0° - 50°C)
	0 - 20 ppm	14.5 psi (1 bar)	32° - 122°F (0° - 50°C)
Peracetic acid	1 - 200 ppm	44 psi (3 bar)	34° - 113°F (1° - 45°C)
	10 - 2,000 ppm	44 psi (3 bar)	34° - 113°F (1° - 45°C)
Hydrogen peroxide	2 - 200 ppm	14.5 psi (1 bar)	32° - 113°F (0° - 50°C)
	20 - 2,000 ppm	14.5 psi (1 bar)	32° - 113°F (0° - 50°C)

NOTE: pH, ORP, Temperature, Conductivity sensors also available. Please consult catalog or factory for selection.

Related Products

DULCOMETER® DMT

The DMT is a compact 2-wire transmitter for measured variables pH, Redox, Conductive Conductivity, Temperature, and Chlorine.

DULCOMETER® Compact

The Compact is an on-line controller/monitor for pH and ORP measurement or control. Control is in one direction only and can be programmed for proportional or PID control. Temperature compensation is available.

DULCOMETER® DDC

The Dulcometer Disinfection Controller is a measuring and control system for up to five variables including pH, ORP, Temperature, Free Chlorine and Total Chlorine. A central DDC unit can control up to 16 remote locations.

ProMinent®

ProMinent Fluid Controls, Inc. (US)
 136 Industry Drive
 Pittsburgh, PA 15275-1014
 Tel: (412) 787-2484
 Fax: (412) 787-0704
 eMail: sales@prominent.us
 www.prominent.us

ProMinent Fluid Controls Ltd. (Canada)
 490 Southgate Drive
 Guelph, ON N1G 4P5
 Tel: 1-888-709-9933 | (519) 836-5692
 Fax: (519) 836-5226
 eMail: sales@prominent.ca
 www.prominent.ca