

ProMinent® Gamma/L Series

Solenoid Driven Diaphragm Type Metering Pump

Programmable - Reliable - Flexible

Flow rates up to 8.4 GPH (32 L/h) and Pressures up to 253 psi (17.5 bar)

Description

The ProMinent Gamma/L series pumps are solenoid driven metering pumps with a mechanically actuated diaphragm-type liquid end. It is constructed of a rugged metal inner casing for components subjected to mechanical stress, and a corrosion resistant plastic outer housing. The standard materials for the liquid end are PVDF or 316 stainless steel, both with PTFE seals.

Gamma/L pumps are designed with a convex DEVELOPAN diaphragm which seals to a concave curve in the liquid end. This allows for precise metering of media with various viscosities and reduces stress for long diaphragm life.



ProMinent® Gamma/L

Benefits

- Self degassing liquid end ideal for feeding **bleach (Sodium Hypo - NaOCl)**
- Low cost, PVDF liquid ends for **maximum chemical compatibility across a wide range of applications**
- Microprocessor based technology for **flexible control & easy timed programming via USB interface with PC**
- Capable of handling up to 3000 cps for **highly visous media such as polymers**
- New optional flow monitor for constant **flow and feed verification**
- Integrated calibration and displays for **accurate chemical usage** and **simplified adjustments**

Liquid End Materials of Construction

Version	Liquid End	Suction/Discharge valves	Seals	Valve balls	Diaphragm*
PPE	Polypropylene	Polypropylene	EPDM	Ceramic	PTFE
PPB	Polypropylene	Polypropylene	Viton®	Ceramic	PTFE
PCE	PVC	PVC	EPDM	Ceramic	PTFE
PCB	PVC	PVC	Viton®	Ceramic	PTFE
NPE	Acrylic	PVC	EPDM	Ceramic	PTFE
NPB	Acrylic	PVC	Viton®	Ceramic	PTFE
PVT	PVDF	PVDF	PTFE	Ceramic	PTFE
TTT	PTFE with carbon	PTFE with Carbon	PTFE	Ceramic	PTFE
SST	316 Stainless steel	316 Stainless Steel	PTFE	Ceramic	PTFE

Auto-degassing type with Hastelloy C valve spring and PVDF valve seat.

Viton® is a registered trademark of DuPont Dow Elastomers.

*Other materials available for special applications.

ProMinent® Gamma/L Series

Solenoid Driven Diaphragm Type Metering Pump

Technical Data: gamma/L

Pump Version	Capacity at Maximum Backpressure					Capacity at 1/2 Maximum Backpressure					Pre-Primed Suction Lift		Max. Stroking Rate spm	Suction/Discharge Tubing Connectors** O.D. x I.D. inches	Shipping Weight (higher weights are for SS)	
	U.S. GPH		L/h		mL/ stroke	U.S. GPH		L/h		mL/ stroke						
	psig	(bar)				psig	(bar)				ft.	(m)				
GALa																
1000	145	(10)	0.19	(0.74)	0.07	73	(5)	0.21	(0.82)	0.08	19.6	(6)	180	1/4 x 3/16	7.5-8.6	(3.4-3.9)
1601	253	(17.5)	0.29	(1.1)	0.10	126	(8.75)	0.37	(1.4)	0.13	19.6	(6)	180	1/4 x 3/16	7.5-8.6	(3.4-3.9)
1602	253	(17.5)	0.55	(2.1)	0.19	126	(8.75)	0.66	(2.5)	0.24	19.6	(6)	180	1/4 x 3/16	7.5-8.8	(3.4-4.0)
1005	145	(10)	1.1	(4.4)	0.41	73	(5)	1.32	(5.0)	0.46	19.6	(6)	180	1/2 x 3/8	7.7-9.0	(3.5-4.1)
0708	101	(7)	1.9	(7.1)	0.66	50.5	(3.5)	2.22	(8.4)	0.78	19.6	(6)	180	1/2 x 3/8	7.7-11.0	(3.5-5.0)
0413	58	(4)	3.2	(12.3)	1.14	29	(2)	3.75	(14.2)	1.31	9.8	(3)	180	1/2 x 3/8	7.7-11.0	(3.5-5.0)
0220	29	(2)	5.0	(19.0)	1.76	14.5	(1)	5.52	(20.9)	1.94	6.5	(2)	180	1/2 x 3/8	7.7-11.0	(3.5-5.0)
1605	253	(17.5)	1.1	(4.1)	0.38	126	(8.75)	1.29	(4.9)	0.45	19.6	(6)	180	1/2 x 3/8	9.3-10.8	(4.2-4.9)
1008	145	(10)	1.8	(6.8)	0.63	73	(5)	2.19	(8.3)	0.76	19.6	(6)	180	1/2 x 3/8	9.5-12.8	(4.3-5.8)
0713	101	(7)	2.9	(11.0)	1.02	50.5	(3.5)	3.46	(13.1)	1.21	13.1	(4)	180	1/2 x 3/8	9.5-12.8	(4.3-5.8)
0420	58	(4)	4.5	(17.1)	1.58	29	(2)	5.04	(19.1)	1.77	9.8	(3)	180	1/2 x 3/8	9.5-12.8	(4.3-5.8)
0232*	29	(2)	8.4	(32.0)	2.96	14.5	(1)	9.56	(36.2)	3.35	6.5	(2)	180	1/2 x 3/8	9.9-13.9	(4.5-6.3)
GALa with auto-degassing liquid ends																
1601	253	(17.5)	0.16	(0.59)	0.055	126	(8.75)	0.21	(0.78)	0.07	5.9	(1.8)	180	1/4 x 3/16	7.7	(3.5)
1602	253	(17.5)	0.37	(1.4)	0.13	126	(8.75)	0.45	(1.7)	0.16	6.9	(2.1)	180	1/4 x 3/16	7.7	(3.5)
1005	145	(10)	0.95	(3.6)	0.33	73	(5)	1.05	(4.0)	0.37	8.8	(2.7)	180	1/2 x 3/8	7.7	(3.5)
0708	101	(7)	1.74	(6.6)	0.61	50.5	(3.5)	1.98	(7.5)	0.69	6.5	(2.0)	180	1/2 x 3/8	7.7	(3.5)
0413	58	(4)	2.8	(10.8)	1.00	29	(2)	3.3	(12.6)	1.17	6.5	(2.0)	180	1/2 x 3/8	7.9	(3.6)
0220	29	(2)	4.3	(16.2)	1.50	14.5	(1)	4.7	(18.0)	1.67	6.5	(2.0)	180	1/2 x 3/8	7.9	(3.6)
1605	253	(17.5)	0.87	(3.3)	0.31	126	(8.75)	1.00	(3.8)	0.35	9.8	(3)	180	1/2 x 3/8	9.5	(4.3)
1008	145	(10)	1.66	(6.3)	0.58	73	(5)	1.98	(7.5)	0.69	9.8	(3)	180	1/2 x 3/8	9.5	(4.3)
0713	101	(7)	2.77	(10.5)	0.97	50.5	(3.5)	3.2	(12.3)	1.14	8.2	(2.5)	180	1/2 x 3/8	9.5	(4.3)
0420	58	(4)	4.12	(15.6)	1.44	29	(2)	4.6	(17.4)	1.61	8.2	(2.5)	180	1/2 x 3/8	9.5	(4.3)

Above capacities and suction lift refer to pumps tested on water at 115 VAC, 60 Hz, and an ambient temperature of 70°F (20°C). Higher specific gravity fluids will reduce suction lift. Higher viscosity fluids will reduce capacity.

Liquid ends for h₂O barb. Positive suction is recommended.

* Not available with bleed valve.

** SS versions use 1/4" female threads except models 0220, 0420, and 0232 which use 3/8" female threads.

Flow Verification: with optional flow monitor

Adjustable metering monitor "Flow Control"

For gamma/L series in material versions PP, PVC, NP and TT. Supplied with connection cable for assembly directly to liquid end.

Monitors individual strokes according to the float and orifice principle. The partial quantity of chemical flowing past the float is adjusted from the total stroke volume via the adjusting screw so that an alarm is actuated if the flow falls below 20%. The user can select the number of incomplete strokes permitted (between 1 and 125) in accordance with the actual process requirements.



ProMinent Fluid Controls, Inc. (USA)
136 Industry Drive
Pittsburgh, PA 15275
Tel: (412) 787-2484
Fax: (412) 787-0704

ProMinent Fluid Controls Ltd. (Canada)
490 Southgate Drive
Guelph, Ontario N1G 4P5
Tel: (519) 836-5692
Fax: (519) 836-5226

Please visit us on the web
www.prominent.us
(Canada) www.prominent.ca
pn: 7750224
NA 5/31/05

ProMinent®