

Chemical Feed Pumps & Systems

Solenoid Driven Metering Pumps



Maximum Capacity and Pressures
Pump Series

	Drive	Type	GPH	psig	l/h	bar
Concept PLUS	S	D	3.93	232	14.9	16
Dulco flex Control - DFXa	M	H	7.92	101.5	30	7
beta/b	S	D	8.45	363	32	25
gamma/ X	S	D	11.9	363	19.7	25
EXtronic ¹	S	D	15.85	363	60	25
gamma/ XL	S	D	21.1	363	80	25
Sigma X: Sigma 1	M	D	38	174	144	12
ProMus*	M	A	101.5	3500	384	241
Dulco flex Control - DFYa ¹	M	H	108.3	116	410	8
Sigma X: Sigma 2	M	D/P	111	232	420	16
Sigma X: Sigma 3	M	D	264	174	1000	12
DulcoFlex DFB	H	H	385	116	1457	8
DulcoFlex DFC ¹	H	H	130 ²	116	492 ²	8
DulcoFlex DFD ¹	H	H	225 ²	232	852 ²	16
Makro TZb ¹	M	D/P/A	529	174	2002	12
Makro/ 5* ¹	M	P	1593	4640	6014	320
Orlita Mf*	M	A	3322	10150	12575	700
Orlita Mh* ¹	M	A	205	43500	777	3000
Orlita PS* ¹	M	P	11904	5800	38076	400
Orlita DR ¹	M	R	1358	5800	5142	400

Notes

* = built in accordance to API 675
¹ = not pictured
² = measured in gpm / l/m

Drives

S = Solenoid
M = Motor

Diaphragm Type

D = Mechanical
P = Packed plunger
H = Hose
A = Hydraulic Actuated

R = Rotary piston



Pre-engineered System



PVT valves



Self-degassing



Safety diaphragm

Motor Driven Metering Pumps



Instrumentation & Specialty Equipment

Measurement and Control Instrumentation

Single & Multi-Channel Controllers



DDC / DULCO net



diaLog DACb



Compact

Cooling Tower & Boiler Controllers



AEGIS II



SlimFlex 5



multiFLEX

DULCOTEST Sensors



Amperometric



Potentiometric



ProMix-M (B controls)

Specialty Products and Engineered Systems



Bello Zon



ProMix-C



Control Panels



PolyRex

© 2018 ProMinent Fluid Controls, Inc. All Rights Reserved. PN: 7750029 General.indd rev7 10/31/2019